

Digital precision with analog soul – an external DAC that reveals the beauty of your digital sources

Designed to expand your audio setup, this DAC significantly enhances the performance of any analog amplifier. It's the perfect addition for those seeking uncompromising fidelity and analog-like musicality from digital sources. The clear interface displays essential playback parameters, and broad format support ensures seamless compatibility with all modern digital content.



SIGNAL PROCESSING SPECIFICATIONS

DAC Chip	ES9039MSPRO (8 mono DACs summed to 2 channels)
Max. Sampling Frequency	768kHz
DSD support	Yes
MQA support	Yes
PCM filters	7 selectable filters
Frequency Response	20 Hz – 20 kHz (<0.1dB @ 48kHz)
Total Harmonic Distortion + Noise (THD+N)	<0,0001% (1kHz @ 0dBFS)
Signal-to-Noise Ratio (SNR)	>125dB (1kHz @ 0dBFS)

INPUTS / OUTPUTS

Digital Inputs	2 × USB Type B (galvanically isolated) 1 × Optical 1 × Coaxial RCA 1 × Coaxial BNC 1 × AES/EBU
Analog outputs	1 × RCA 1 × Balanced XLR
Rated output voltage	2.3 V _{RMS} (RCA, XLR)
Trigger (12 V)	In, Out

GENERAL

Dimensions	440 × 369 × 65 mm
Maximum Power Consumption	12 W
Standby Power Consumption	<0,5 W
Power supply type	Linear power supply with toroidal transformer
Available Colors	Silver, Black
Package Contents	Power cable, remote control with battery, user manual, warranty card